

Apertura scheda gwCalendar

La gwCalendar è una particolare tipologia di scheda descritta [qui](#).

openGwCalendarTab()

Per aprire questa tipologia di tab è esposta l'apposita function openGwCalendarTab().

Parametri

- **title** String, optional
- **params** Object, required
 - **calendarCodes** String, array: comma separated values
 - **eventClassName** String, array: comma separated values. parallel array to **calendarCodes** (each n position refers to nth calendarCodes's one)
 - **filters** Object or Object[], optional *removable* filters. Inside filters columnName property are available some predefined placeholders: '#id_event#', '#cod_event#', '#summary#', '#place#', '#start_date#', '#end_date#', '#notes#', '#notes#', '#cod_calendar#', '#cod_event_status#', '#cod_priority#', '#cod_event_type#'. This can be used to make filters shared with different gwClasses implementing the event interface (each one that may overrides some field through a specific mapping). Simple filter based on a specific (=gwClass related) columnName, for example evt_id_event instead of the default id_event still will works, but gwClass cross compatibility may not be granted. Ex:

```
{condition: 'AND', columnName: '#cod_event_status#', operator: '=', filterType: 'STRING', value: 'CLO'}
```

- **staticFilters** Object or Object[], optional *fixed* filters. Inside filters columnName property are available some predefined placeholders: '#id_event#', '#cod_event#', '#summary#', '#place#', '#start_date#', '#end_date#', '#notes#', '#notes#', '#cod_calendar#', '#cod_event_status#', '#cod_priority#', '#cod_event_type#'. This can be used to make filters shared with different gwClasses implementing the event interface (each one that may overrides some field through a specific mapping). Simple filter based on a specific (=gwClass related) columnName, for example evt_id_event instead of the default id_event still will works, but gwClass cross compatibility may not be granted. Ex:

```
{condition: 'AND', columnName: '#cod_event_type#', operator: '=', filterType: 'STRING', value: 'ETP3'}
```

- **minHours** Integer, optional, in range [0, 23], 8 default. Min hours shown is day view
- **maxHours** Integer, optional, in range [1, 36], 16 default. Max hours shown is day view
- **date** Date, optional: ex: value="new Date(2015, 26, 3)". If not set today is used. new Date() takes 3 parameters, in order: year, month, day
- **dateInterval** String, optional, default 'week'. possible options: 'day', 'week', 'month'
- **dateIntervalSteps** Integer, optional, default 5. n days from the reference date

Gli ultimi 5 parametri sono ripresi direttamente fra quelli esposti da dojo, ed influiscono sulla grafica

della scheda Calendario. Sono opzionali, e in caso di omissione sono utilizzati dei valori di default. Essi agiscono come descritto nella documentazione ufficiale visualizzabile [qui](#).

- **insertIndex** Integer, opzionale. Determina in quale posizione verrà aperta la scheda. Se omesso la scheda verrà aperta a destra, in ultima posizione

Esempi

Codice minimale.

example.js

```
var title = 'Calendar Events';
var params = {
    calendarCodes: 'CAL1,CAL2', //array: comma separated values
    eventClassName: 'class_name_1,class_name_2' //array: comma
    separated values. parallel array to calendarCodes
};
var gwCalendarTab = openGwCalendarTab(title, params);
```

Esempio con utilizzo di tutti i parametri, anche opzionali

example.js

```
var title = 'Title';
var tabWidgetSuffixId = 'cal_name'; //Optional, Used to eventually
reuse an already opened tab. if omitted a random one is generated, and
a new tab is opened
var title = 'Calendar Events';
var params = {
    calendarCodes: 'CAL1,CAL2', //array: comma separated values
    eventClassName: 'class_name_1,class_name_2', //array: comma
    separated values. parallel array to calendarCodes
    filters: {condition: 'AND', columnName: '#cod_event_status#',
operator: '=', filterType: 'STRING', value: 'CLO'},
    staticFilters: {condition: 'AND', columnName: '#cod_event_type#',
operator: '=', filterType: 'STRING', value: 'ETP3'},
    minHours: 0, //Integer, optional, default 0. min hours shown is day
view
    maxHours: 23, //Integer, optional, default 23. Max hours shown is
day view
    date: null, // Optional: ex: value="new Date(2015, 26, 3)". If not
set today is used. new Date() takes 3 parameters, in order: year,
month, day
    dateInterval: 'week', //String, optional, default 'week'. possible
options: 'day', 'week', 'month'
    dateIntervalSteps: 5 //Integer, optional, default 5. n days from
the reference date
```

```
};

var gwCalendarTab = openGwCalendarTab(title, params);
```

Esempio apertura calendario con filtri presi da lista classe filtrata, aprendolo sulla prima data utile:

example.js

```
// Available incoming parameters:
//   In the linkList grid parameter has been added: start class id and
//   name, start class key column and key column type,
//   target class name, target class attribute id and target class key
//   column.
//   /*String*/ gwClassName, /*Object*/ queryParameter, /*Object*/
grid, /*Object*/ detailContainerId
//debugger;

var filters = []
if(grid.query && grid.query.query){
    filters = grid.query.query.filters || [];
    if(grid.query.query.staticFilters) filters = [filters,
...grid.query.query.staticFilters]; //TODO MERGE STATICFILTERS BETTER
}
var sort = null;
var callback = function(items){
    var openingDate = items.length!=null ? new
Date(items[0].evt_start_date) : new Date();

    var itemIdList = [];
    items.forEach(function(item){
        itemIdList.push(item[grid.store.objectStore.idProperty]);

        if(new Date(item.evt_start_date) < openingDate) openingDate =
new Date(item.evt_start_date);
    });
    var filters = [{condition: 'AND', columnName: '#id_event#',
operator: 'IN', filterType: 'INTEGER', value: itemIdList}];

    var title = 'Calendario Eventi';
    var tabWidgetSuffixId = gwClassName+'_filtered'; //Optional, Used
to eventually reuse an already opened tab. if omitted a random one is
generated, and a new tab is opened
    var params = {
        calendarCodes: 'PEM_ASS,PEM_BUI,PEM_IMP,PEM_SPA', //array:
comma separated values
        eventClassName:
gwClassName+', '+gwClassName+', '+gwClassName+', '+gwClassName, //array:
comma separated values. parallel array to calendarCodes
        filters: filters,
        staticFilters: [],
```

```
        minHours: 0, //Integer, optional, default 0. min hours shown is day view
        maxHours: 23, //Integer, optional, default 23. Max hours shown is day view
        date: openingDate, // Optional: ex: value="new Date(2015, 26, 3)". If not set today is used. new Date() takes 3 parameters, in order: year, month, day
        dateInterval: 'month', //String, optional, default 'week'.
        possible options: 'day', 'week', 'month'
        dateIntervalSteps: null //Integer, optional, default 5. n days from the reference date
    };
    var gwCalendarTab = openGwCalendarTab(title, params);
};

selectGwClassRecords(gwClassName, filters, sort, callback); //4.5.* and 4.4.*
//selectGwClassRecordsRaw(gwClassName, filters, sort, callback); //from 4.6.8
```

From:
<https://wiki.geowebframework.com/> - **GeowebFramework**



Permanent link:
https://wiki.geowebframework.com/doku.php?id=custom:api_js_opengwcalendartab

Last update: **2024/11/04 16:38**